




3D02-2



3D03-1

DRYER LIMIT ONE SHOT THERMAL FUSE (TCO)

Assembled With Spade Terminals

FEATURES

- One shot operation cuts off electrical current.
- High current interrupt capacity.
- Low resistance.
- Compact size facilitates mounting in confined spaces.
- Special configurations and mounting packages available.

SPECIFICATIONS

Electrical Rating 115v AC/15.0A
250v AC/10.0A

Model Number	Open Temperature	Therm-O-Disc Style No.
3D02-1	243°F	G4AP0402117C
3D02-2	196°F	G4AP0400144C
3D03-1	196°F	G4AP0503084C
3D03-2	183°F	G4AP0100084C



3D04-1

DRYER LIMIT THERMOSTAT

1/2" Disc Snap-Action

FEATURES

- Single operation high speed contact separation.
- Large flange air stream/surface mount.

SPECIFICATIONS

Electrical Rating 120v AC/15.0A
240v AC/10.0A

Model Number	Open Temperature	Auto Reclose Below	Disc Type	Therm-O-Disc Style No.
3D04-1	222° ± 8°F	-35°C/-31°F	Enclosed Aluminum Cup	36F24 20025
3D04-2	300° ± 11°F	-35°C/-31°F	Enclosed Stainless Steel Cup	36F14 20021



F91-3889



F91-3890

2500 SERIES REPLACEMENT GAS VALVE COILS

FEATURES

- Easy installation of replacement coil assemblies.
- Available for most popular models.
- Single or complete coil sets

Model Number	Application	Description	OEM Type
F91-3889	25M01A-xxx	120V Secondary Coil Replacement for 25M Valve Individual Pack Secondary Coil	Used on Whirlpool, GE, Maytag, Speed Queen,
F91-3890	25M01A-xxx	120V Coil Replacement for Booster and Holding Coil	Fridgidaire, Amana, current production (since 1985)